



M2 Comfort Plus mono/duo NC



TRANSMIT

Microfone:

Frequency:

Sensitivity:

Noice Canceling (NC)

100 Hz – 4 kHz

-45 dB/Pa+/-2 dB 4,4 kOhm Load

Operating voltage:

1,2 – 8V DC

M2 Comfort Plus mono/duo NC



Receive

Speaker:

Dynamic

Input impedance:

150 Ω \pm 15%

Frequency response:

33 Hz – 17 kHz

Sensitivity:

90 \pm 2dB

General

Operating temperature:

0 to 50°C

Polarity:

Microphone polarised

Cable length:

0,7 - 2,5m

Weight (w/o cable):

- mono 46g
- duo 48g

M3 Optimum mono/duo NC



TRANSMIT

Microfone:

Frequency:

Sensitivity:

Noice Canceling (NC)

30 Hz – 17 kHz

-45 dB/Pa+/-3 dB 4,4 kOhm Load

Operating voltage:

1,2 – 8V DC

M3 Optimum mono/duo NC



Receive

Speaker:

Dynamic

Input impedance:

150 Ω \pm 15%

Frequency response:

35 Hz – 4,5 kHz

Sensitivity:

83 \pm 2dB

General

Operating temperature:

0 to 50°C

Polarity:

Microphone polarised

Cable length:

0,7 - 2,5m

Weight (w/o cable):

- mono 45g
- duo 49g

M5 Modular mono/duo NC



TRANSMIT

Microfone:

Frequency:

Sensitivity:

Ultra Noise Canceling (UNC)

100 Hz – 4 kHz

-47 dB/Pa+/-3 dB 8 kOhm Load

Operating voltage:

1,2 – 8V DC

M5 Modular mono/duo NC



Receive

Speaker:

Dynamic

Input impedance:

150 Ω \pm 15%

Frequency response:

35 Hz – 4,5 kHz

Sensitivity:

83 \pm 2dB

General

Operating temperature:

0 to 50°C

Polarity:

Microphone polarised

Cable length:

0,7 - 2,5m

Weight (w/o cable):

- mono 42g
- duo 47g

M6 Advanced mono NC



TRANSMIT

Microfone:

Frequency:

Sensitivity:

Ultra Noise Canceling (UNC)

20 Hz – 16 kHz

-43 dB/Pa+/-3 dB 8 kOhm Load

Operating voltage:

1,2 – 8V DC

M6 Advanced mono NC



Receive

Speaker:

Dynamic

Input impedance:

150 Ω \pm 15%

Frequency response:

300 Hz – 5 kHz

Sensitivity:

102 \pm 2dB

General

Operating temperature:

0 to 50°C

Polarity:

Microphone polarised

Cable length:

0,7 - 2,5m

Weight (w/o cable):

- mono 65g